



Габаритные, установочные и присоединительные размеры.
Электродвигатели малой мощности. IM 1081, IM 1082, IM 2081, IM 2082.

Тип двигателя	L, mm	l1, mm	l2, mm	l10, mm	l11, mm	l30, mm	l33, mm	b, mm	b1, mm	b2, mm	b10, mm	b30, mm	h, mm
4A-90L-2	405	50	50	125	155	350	56	175	8	8	140	204	90
4A-90L-4	405	50	50	125	155	350	56	175	8	8	140	204	90
4A-90S-6	-	50	-	125	155	350	56	175	8	-	140	204	90
АШ-90-2 *	-	50	-	125	155	350	56	175	8	-	140	204	90
АШ-90-2 *	-	50	-	125	155	350	56	175	8	-	140	204	90
АО4-100L-2	-	60	-	140	175	400	63	200	8	-	160	224	100
АО4-100LK-2	-	60	-	140	175	400	63	200	8	-	160	224	100
Тип двигателя	h1, mm	h2, mm	h5, mm	h6, mm	h31, mm	d1, mm	d2, mm	d3, mm	d10, mm	d20, mm	d30, mm	n	x
4A-90L-2	7	7	27	27	240	24	24	10	-	-	-	4	x
4A-90L-4	7	7	27	27	240	24	24	10	-	-	-	4	x
4A-90S-6	7	-	27	-	240	24	-	10	180	215	250	4	x
АШ-90-2 *	7	-	27	-	240	24	-	10	-	-	-	4	x
АШ-90-2 *	7	-	27	-	240	24	-	10	180	215	250	4	x
АО4-100L-2	7	-	31	-	260	28	-	12	180	215	250	4	x
АО4-100LK-2	7	-	31	-	260	28	-	12	180	215	250	4	x

* - однофазные электродвигатели.